

SMART PUBLIC CHARGER 2 x 22 kW, 3-phase, wall-mounted



COMPACT DESIGN

Attractive appearance, simple but elegant



FULL PROTECTION

Complex electrical protection, over/under temperature protection, residual current protection



GLOBAL STANDARD

OCPP v1.6 open charge point protocol. IEC 62196 type II connector



STABLE

IP65 protection grade, capable for harsh environmental conditions



CERTIFICATION

Certificate

CE



EASY TO INSTALL



Wall-mounting or pole-mounting



MECHANICAL

Dimension (W/H/D) 360 / 562 / 175 mm

Weight < 24,5 KG



SMART PUBLIC CHARGER 2 x 22 kW, 3-phase, wall-mounted

<p>Input & Output</p> <p>Input voltage Output frequency Output voltage Max output power Max output current Charging interface type Connection Number of connection</p>	<p>400V AC 50/60Hz 400V AC 22 KW x 2 32A x 2 IEC 62196-2, Type II 2 x Sockets / 2 x 5m cables 2</p>
<p>Protection</p> <p>Over voltage protection Under voltage protection Overload protection Short circuit protection Earth leakage protection Over-temperature protection Surge protection</p>	<p>Yes Yes Yes Yes TypeA+6mA DC Fault current protection Yes Yes</p>
<p>Function & Accessory</p> <p>Ethernet / WIFI / 4G Payment support RCD LED indicator light Intelligent power adjustment Integrated smart meter Emergency stop button RFID</p>	<p>Yes / Opt / Yes RFID / QR (standard) Free / APP Mega Mobility Type A + 6mA DC fault current protection (equivalent to Type B) Yes Opt Opt Yes Yes</p>
<p>Working environment</p> <p>Protection degree Environment temperature Relative humidity Maximum altitude Cooling Standby power</p>	<p>IP55 -25°C ~ +50°C 5 – 95% non-condensing <2000 m Natural air cooling <8W</p>
<p>Mechanical</p> <p>Dimension (W / H / D) Weight</p>	<p>360 / 562 / 175 mm With sockets: < 22 kg With cables: < 24,5 kg</p>
<p>Certification</p> <p>Certificate</p>	<p>CE</p>

